ZOONLAB

ANIMAL HUSBANDRY EXPERTS

PRODUCT SPECIFICATION / DATA SHEET

Mobile Veterinary Large-Animal Autopsy Table

PRODUCT / APPLICATION

Mobile veterinary large-animal autopsy table for veterinary pathology, zoology and museum specimen preparation, including transport, autopsy and dissection of large animals.



DESCRIPTION

Heavy-duty construction, entirely made of stainless steel EN/DIN 1.4301 (optional 1.4571). Maximum load capacity 1,500 kg with four electrically controlled lifting columns. Higher load capacity without lifting columns: please contact us. Mobile design with lockable heavy-duty castors.

Designed for veterinary pathology, food monitoring and museum specimen preparation. The upper section is designed for the high loads imposed by large animals. The work surface is convex (raised in the middle) and has two outlets, 100 mm in diameter, and two removable residual sieves. Wastewater drains into a collection pipe approximately 300 mm above the floor (alternative: stainless steel containers). The entire work surface is sound-insulated.



Four removable fixation rods with fastening eyelets are provided for safe transport. The lower section contains four splash-water-protected heavy-duty lifting columns for stepless height adjustment over 300 mm using two synchronized switches marked UP and DOWN. The columns operate synchronously even under uneven loads. Power supply via Schuko plug with approx. 4 m cable; optional casters.

TECHNICAL DATA

Material: Stainless steel EN/DIN 1.4301, K320 duplex finish
Weight: approx. 450 kg
Maximum load: 1,500 kg
Dimensions: 2,000 mm (L) x 1,000 mm (W) x 800-1,100 mm (H), without fixation rods
Fixation rods: 700 mm long
Height control: Electric synchronous control, protection class IP66
Work surface: Convex, with 2 x DN 100 drains and 2 removable waste sieves, sound-insulated underneath
Controls: Handheld control unit; interface for speed setting and shut-off
Ergonomics: Convenient raising/lowering for ergonomic work
Lifting columns: 4 electronic lifting columns, IPX1, lifting force 4,300 N
Other features: H2O2-fumigable; disinfectable
Castors: 4 castors, steerable and lockable, diameter 200 mm
Power: Battery-powered electric supply incl. charger





ZOONLAB GmbH | Hermannstrasse 6 | 44579 Castrop-Rauxel | Germany
T +49 (0) 2305 97304-0 | info@zoonlab.de | www.zoonlab.de